

# VOLVO PENTA

**Volvo Penta of the Americas**  
1300 Volvo Penta Drive  
Chesapeake, Virginia 23320-9810

## Service Bulletin

|             |           |           |
|-------------|-----------|-----------|
| Group       | Number    | Version   |
| <b>44-1</b> | <b>71</b> | <b>02</b> |

### Gear Lube All Engines

Distribution: M      Date: 02-2008      Binder: A, B, C,

It is essential that the correct oil is used in sterndrives for reliable operation. This offers increased service life.

Where engine oils can be used, we have noted this in the table below. The oil is the same as for the engine. This means the same oil as is recommended for each engine (petrol/gasoline) may also be used for the transmission.

| <i>Drive</i>   |  |                             |                          |
|--|--|-----------------------------|--------------------------|
| Model  | Oil Grade/Recommendation                   | Part No.<br>(North America) | Part No.<br>(Outside NA) |
| SP Drive:<br>100B, 200, 250,<br>270, 275, 280, 285,<br>290, SP-A, SP-A1,<br>SP-A2 <sup>1</sup> , SP-C <sup>1</sup> | Same as for engine                         | –                           | –                        |
| DP Drive:<br>280, 290, DP-A,<br>DP-A1  | Mineral, API GL5 <sup>2</sup> (SAE 80W/90) | 1141676                     | 1141637                  |
| DP-A2, DP-B,<br>DP-B1, DP-C,<br>DP-D, DP-E, DPX  | Fully synthetic, API GL5                   | 1141679                     | 1141634                  |
| DP-S, DPS  | Fully synthetic, API GL5                   | 1141679                     | 1141634                  |
| DPH, DPR, IPS  | Fully synthetic, API GL5                   | 1141679                     | 1141634                  |
| DP-G   | Fully synthetic, API GL5                   | 1141666                     | 1141666                  |
| SX   | Fully synthetic, API GL5                   | 1141679                     | 1141634                  |
| XDP  | Fully synthetic, API GL5                   | 1141679                     | 1141634                  |

1. SP-A2 and SP-C may also be operated on fully synthetic, API GL5, except ratio 2.15:1.
2. **Note!** If the drive was manufactured before 1986, for a 30 or 40 engine, and has previously been operated with engine oil in the drive, engine oil should be used in future.